



Martin's industry-standard Jem Roadie X-Stream is now available in a high-output, compact version.

PHYSICAL	Length: 800 mm (31.5 in.) Width: 500 mm (19.7 in.) Height: 600 mm (23.6 in.) Dry weight: 80 kg (176.4 lbs.)
PERFORMANCE	Max. fog output (approx.): 2500 m ³ per minute Max. operating time at full output (approx.): 90 minutes Operating time: Continuous, automatic level adjustment Warm-up time (approx.): 9 minutes
CONTROL AND PROGRAMMING	Control options: Onboard control panel, DMX Compatible remote controls: For limited control DMX channels: 2 (output and fan) Protocol: USITT DMX512/1990
CONSTRUCTION	Housing: Steel & aluminum Heat exchanger: 2 x 1500 W, direct thermal protection
FLUID SYSTEM	Fluid pump: Oscillating piston, high pressure X2 Onboard fluid capacity: 9.5 l Fluid consumption at peak output: 220 ml per minute
INSTALLATION	Orientation: Floor mount (Horizontal or vertical) or flying kit
CONNECTIONS	Remote control: 3-pin locking XLR DMX data: 3-pin and 5-pin XLR sockets Power cable entry: Hard-wired
ELECTRICAL	AC power: 208 V 60 Hz / 220 - 240 V 50 Hz Main fuse (208-240 V power): Onboard 16 A Breaker
TYPICAL POWER AND CURRENT	208 V, 60 Hz: 2450 W, 12.7 A 220 V, 50 Hz: 2745 W, 12.5 A 230 V, 50 Hz: 3000 W, 13.04 A 240 V, 50 Hz: 3267 W, 13.6 A <i>Measurements made at nominal voltage. Allow for a deviation of +/- 10%.</i>
THERMAL	Maximum ambient temperature (Ta max.): 40° C (104° F) Exterior surface temperature, steady state: 50° C (122° F) Max. nozzle temperature: 200° C (392° F)
APPROVALS	EU safety: EN 50 081-1, EN 50 082-1 EU safety: EN 60 335-1 (1995)
INCLUDED ITEMS	User manual: P/N 35010027 Container 9.5 l: P/N 34300528 Hard wired mains cable 2 m (6.6 ft.): Flying kit:
ACCESSORIES	Pro Smoke Studio (DX Mix) fluid Pro Smoke Super (ZR Mix) fluid Pro Smoke High Density (SP Mix) fluid Pro Steam Simulation (AA) fluid Regular DJ (DJ mix) fluid

I-fog fluid

Roadie Compact remote control unit: P/N 92765031

ORDERING INFORMATION

Jem Roadie Compact: P/N 92230500

Published on: 23 Nov 2007. © 2007 Martin Professional A/S. Specifications subject to change without notice